

### Features

- Full port design for unrestricted flow
- 316SS 2-piece investment cast body
- RTFE (reinforced Teflon) ball seats
- Triple PTFE/Viton live loaded stem seals, adjustable
- Silicone free
- Valves tested accordance with API 598
- Rugged aluminum Type 4X weatherproof enclosure
- Heavy duty motor with overload protection
- Manual override with end of travel mechanical stops
- Two auxiliary limit switches included with on-off units
- EPS - Electronic Positioning System models available
- Actuators CSA Listed per UL429 and CSA C22.2 and Explosion ratings per Approvals section
- Electrical interface: Two 1/2" NPT threaded ports with temporary plugs. Remove and replace with corresponding explosion proof cable connectors, pipe or plugs (Not Included)

### Applications

On-Off or modulating control (with EPS) of water, air, oil and other media compatible with the materials of construction. Suitable for vacuum service up to 29inchHg. Actuator designed for 70% duty cycle.

### Operation

On-Off electric actuated valve uses power-to-open and power-to-close, stays in the last known position with loss of power. On receipt of a continuous voltage signal, the motor runs and via a rugged all metal gear system rotates the ball 90°. The motor is automatically stopped by internal cams striking limit switches. On receipt of a reversing continuous signal, the motor turns in the opposite direction reversing the valve position. Valves with EPS-Electronic Positioning System provide 0-100% control of flow via a 4-20mA input control signal.

### Construction

|                                 |                                                              |
|---------------------------------|--------------------------------------------------------------|
| Valve Body                      | 316SS ASTM A351, CF8M                                        |
| Ball/Stem/End Caps              | 316SS CF8M                                                   |
| Ball Seats                      | RTFE (reinforced Teflon)                                     |
| Stem Seals                      | PTFE/Viton                                                   |
| Gear Drive                      | Heavy duty alloy steel/aluminium bronze, self locking        |
| Actuator Enclosure              | Anti-corrosive durable painted aluminum alloy, Type 4X/ IP67 |
| Visual Valve Position Indicator | High strength glass lens                                     |
| Fasteners                       | Stainless Steel                                              |
| Auxiliary Limit Switches        | 2 x SPDT (5A/125VAC), on-off actuators only                  |



### Description

Explosion Proof 2-piece stainless steel full port ball valves are investment cast with unrestricted flow and minimum pressure loss. Adjustable live loaded stem seal packing helps compensate for wear, pressure and/or temperature fluctuations, extending the cycle life of the valve. Rugged Type 4X explosion proof electric actuator includes a manual override, valve position confirmation switches (on-off models), over-torque protection. EPS positioner models allow positioning of the ball with a 4-20mA input control signal.

### Approvals- Actuators

#### ANTI EXPLOSION GRADE



The anti-explosion grade of these actuators is

- ♦ Class 1, Division 1, Groups C & D T5
- ♦ Ex db IIC T5 Gb Class 1 Zone 1
- ♦ AEx db IIC T5 Gb

Where:

Class I – Hazard Class  
Division 1/ Zone 1 – Area Classification  
db – Explosion Proof Type  
II – Electrical Equipment design for explosive atmospheres (except colliery)  
C – Magnitude of the explosion  
T5 - Highest allowed surface temperature of the actuator (+ 55C)  
Gb – Protection Grade  
The grades of combustible gas, steam and temperature group are listed in CSA 22.2 No 60079-0-2019, CSA 22.2 No 60079-1-2016, CSA 22.2 No 30-M1986(R2016), CSA 22.2 No 145-11(R2015), ANSI/UL 60079-2:2020, ANSI/UL 1203-2013, ANSI/UL 674 Fifth Edition. It is the user's responsibility to ensure compatibility with the applicable regulations.

CE- EN 60204-1:2006

### Standards- Valves

- CE- PED 2014/68/UE
- Design: API 608
- Testing: API 598
- Threaded Connection: ASME B1.20.1 (NPT)/ ISO 228-1/ BS21
- Pressure/Temperature Rating: ASME B16.34
- Marking: MSS SP-25

### Construction Features

Auxiliary Limit Switches(2)  
for confirming valve position,  
on-off versions

Heavy duty integral motor  
design significantly reduces  
physical size of actuator

Rugged durable painted  
aluminum Type 4X/ IP67  
weatherproof enclosure.

High strength glass position indi-  
cator

Circular field joints for superior  
explosion-proof reliability

Manual Override with protective  
cover

Self-locking all metal gear drive,  
no additional brake required

Machined 316SS ball

Investment casting 316 stainless  
steel valve body and end caps

Triple PTFE/Viton live  
loaded stem seals

RTFE (Reinforced Teflon) ball  
seats

### Pressure Rating

**Pressure Rating\***: 1000 PSI (69 Bar) (1/4"-2")  
800 PSI (55 Bar) (2-1/2"-4") CWP non-shock, Vacuum 29inHg  
\* See P/T chart

### Temperature Rating

Actuator Temperature Rating: -13 to 131° F (-25 to 55° C)

Valve Temperature Rating: -4 to 392° F (-20 to 200°C)

\* See P/T chart



Visual Valve  
Position Indicator

**Installation Requires-Two 1/2" NPT threaded explosion-proof connectors or pipe for electrical interface**

**(\*\*Not included\*\*)**

## Specifications (English units)

| Stock Number                                                           | Pipe Size (NPT) | Orifice Diameter (inch) | Cv Flow Factor* | Max Pressure (PSI)** | Cycle Time/ 90° (seconds) | Voltage          | Current (amps) | Duty Cycle | Electrical Dwg. |
|------------------------------------------------------------------------|-----------------|-------------------------|-----------------|----------------------|---------------------------|------------------|----------------|------------|-----------------|
| <b>110 VAC ELECTRIC ACTUATED STAINLESS BALL VALVES, ON-OFF version</b> |                 |                         |                 |                      |                           |                  |                |            |                 |
| 585202                                                                 | 1/4             | 0.5                     | 6.9             | 1000                 | 20                        | 110 VAC, 50/60Hz | 0.27           | 70%        | B               |
| 585203                                                                 | 3/8             | 0.5                     | 6.9             | 1000                 | 20                        | 110 VAC, 50/60Hz | 0.27           | 70%        | B               |
| 585204                                                                 | 1/2             | 0.6                     | 9.7             | 1000                 | 20                        | 110 VAC, 50/60Hz | 0.27           | 70%        | B               |
| 585206                                                                 | 3/4             | 0.8                     | 18.4            | 1000                 | 20                        | 110 VAC, 50/60Hz | 0.27           | 70%        | B               |
| 585208                                                                 | 1               | 1.0                     | 55.4            | 1000                 | 20                        | 110 VAC, 50/60Hz | 0.27           | 70%        | B               |
| 585210                                                                 | 1-1/4           | 1.3                     | 89.7            | 1000                 | 20                        | 110 VAC, 50/60Hz | 0.27           | 70%        | B               |
| 585212                                                                 | 1-1/2           | 1.5                     | 144.2           | 1000                 | 20                        | 110 VAC, 50/60Hz | 0.27           | 70%        | B               |
| 585216A                                                                | 2               | 2.0                     | 226.0           | 1000                 | 30                        | 110 VAC, 50/60Hz | 0.63           | 70%        | B               |
| 585220                                                                 | 2-1/2           | 2.6                     | 289.0           | 800                  | 30                        | 110 VAC, 50/60Hz | 0.63           | 70%        | B               |
| 585224                                                                 | 3               | 3.1                     | 454.0           | 800                  | 30                        | 110 VAC, 50/60Hz | 0.63           | 70%        | B               |
| 585232                                                                 | 4               | 3.9                     | 710.0           | 800                  | 30                        | 110 VAC, 50/60Hz | 0.63           | 70%        | B               |
| <b>24 VDC ELECTRIC ACTUATED STAINLESS BALL VALVES, ON-OFF version</b>  |                 |                         |                 |                      |                           |                  |                |            |                 |
| 585302                                                                 | 1/4             | 0.5                     | 6.9             | 1000                 | 20                        | DC24             | 1.8            | 70%        | G               |
| 585303                                                                 | 3/8             | 0.5                     | 6.9             | 1000                 | 20                        | DC24             | 1.8            | 70%        | G               |
| 585304                                                                 | 1/2             | 0.6                     | 9.7             | 1000                 | 20                        | DC24             | 1.8            | 70%        | G               |
| 585306                                                                 | 3/4             | 0.8                     | 18.4            | 1000                 | 20                        | DC24             | 1.8            | 70%        | G               |
| 585308                                                                 | 1               | 1.0                     | 55.4            | 1000                 | 20                        | DC24             | 1.8            | 70%        | G               |
| 585310                                                                 | 1-1/4           | 1.3                     | 89.7            | 1000                 | 20                        | DC24             | 1.8            | 70%        | G               |
| 585312                                                                 | 1-1/2           | 1.5                     | 144.2           | 1000                 | 20                        | DC24             | 1.8            | 70%        | G               |
| 585316A                                                                | 2               | 2.0                     | 226.0           | 1000                 | 30                        | DC24             | 2.4            | 70%        | G               |
| 585320                                                                 | 2-1/2           | 2.6                     | 289.0           | 800                  | 30                        | DC24             | 2.4            | 70%        | G               |
| 585324                                                                 | 3               | 3.1                     | 454.0           | 800                  | 30                        | DC24             | 2.4            | 70%        | G               |
| 585332                                                                 | 4               | 3.9                     | 710.0           | 800                  | 30                        | DC24             | 2.4            | 70%        | G               |

Cv = The GPM of water at 60° F that will pass through the valve with 1 PSI pressure drop

\* Pressure @ 0-100° F (reduced pressure at higher temperatures—see P/T chart)

• Torque at 0 PSI and 75°F

## Specifications (English units)

| Stock Number                                                                        | Pipe Size (NPT) | Orifice Diameter | Cv Flow Factor* | Max Pressure (PSI)** | Cycle Time/ 90° (seconds) | Voltage          | Current (amps) | Duty Cycle | Electrical Dwg. |
|-------------------------------------------------------------------------------------|-----------------|------------------|-----------------|----------------------|---------------------------|------------------|----------------|------------|-----------------|
| <b>110 VAC ELECTRIC ACTUATED STAINLESS BALL VALVES, EPS POSITIONER 4-20mA input</b> |                 |                  |                 |                      |                           |                  |                |            |                 |
| 585402                                                                              | 1/4             | 0.5              | 6.9             | 1000                 | 20                        | 110 VAC, 50/60Hz | 0.27           | 70%        | E               |
| 585403                                                                              | 3/8             | 0.5              | 6.9             | 1000                 | 20                        | 110 VAC, 50/60Hz | 0.27           | 70%        | E               |
| 585404                                                                              | 1/2             | 0.6              | 9.7             | 1000                 | 20                        | 110 VAC, 50/60Hz | 0.27           | 70%        | E               |
| 585406                                                                              | 3/4             | 0.8              | 18.4            | 1000                 | 20                        | 110 VAC, 50/60Hz | 0.27           | 70%        | E               |
| 585408                                                                              | 1               | 1.0              | 55.4            | 1000                 | 20                        | 110 VAC, 50/60Hz | 0.27           | 70%        | E               |
| 585410                                                                              | 1-1/4           | 1.3              | 89.7            | 1000                 | 20                        | 110 VAC, 50/60Hz | 0.27           | 70%        | E               |
| 585412                                                                              | 1-1/2           | 1.5              | 144.2           | 1000                 | 20                        | 110 VAC, 50/60Hz | 0.27           | 70%        | E               |
| 585416A                                                                             | 2               | 2.0              | 226.0           | 1000                 | 30                        | 110 VAC, 50/60Hz | 0.63           | 70%        | E               |
| 585420                                                                              | 2-1/2           | 2.6              | 289.0           | 800                  | 30                        | 110 VAC, 50/60Hz | 0.63           | 70%        | E               |
| 585424                                                                              | 3               | 3.1              | 454.0           | 800                  | 30                        | 110 VAC, 50/60Hz | 0.63           | 70%        | E               |
| 585432                                                                              | 4               | 3.9              | 710.0           | 800                  | 30                        | 110 VAC, 50/60Hz | 0.63           | 70%        | E               |
| <b>24 VDC ELECTRIC ACTUATED STAINLESS BALL VALVES, EPS POSITIONER 4-20mA input</b>  |                 |                  |                 |                      |                           |                  |                |            |                 |
| 585502                                                                              | 1/4             | 0.5              | 6.9             | 1000                 | 20                        | DC24             | 1.8            | 70%        | GEY             |
| 585503                                                                              | 3/8             | 0.5              | 6.9             | 1000                 | 20                        | DC24             | 1.8            | 70%        | GEY             |
| 585504                                                                              | 1/2             | 0.6              | 9.7             | 1000                 | 20                        | DC24             | 1.8            | 70%        | GEY             |
| 585506                                                                              | 3/4             | 0.8              | 18.4            | 1000                 | 20                        | DC24             | 1.8            | 70%        | GEY             |
| 585508                                                                              | 1               | 1.0              | 55.4            | 1000                 | 20                        | DC24             | 1.8            | 70%        | GEY             |
| 585510                                                                              | 1-1/4           | 1.3              | 89.7            | 1000                 | 20                        | DC24             | 1.8            | 70%        | GEY             |
| 585512                                                                              | 1-1/2           | 1.5              | 144.2           | 1000                 | 20                        | DC24             | 1.8            | 70%        | GEY             |
| 585516A                                                                             | 2               | 2.0              | 226.0           | 1000                 | 30                        | DC24             | 2.4            | 70%        | GEY             |
| 585520                                                                              | 2-1/2           | 2.6              | 289.0           | 800                  | 30                        | DC24             | 2.4            | 70%        | GEY             |
| 585524                                                                              | 3               | 3.1              | 454.0           | 800                  | 30                        | DC24             | 2.4            | 70%        | GEY             |
| 585532                                                                              | 4               | 3.9              | 710.0           | 800                  | 30                        | DC24             | 2.4            | 70%        | GEY             |

Cv = The GPM of water at 60° F that will pass through the valve with 1 PSI pressure drop

\* Pressure @ 0-100° F (reduced pressure at higher temperatures—see P/T chart)

• Torque at 0 PSI and 75°F

## Specifications (Metric units)

| Stock Number                                                           | Pipe Size (NPT) | Orifice Diameter | Kv Flow Factor* | Max Pressure (Bar)** | Cycle Time/90° (seconds) | Voltage          | Current (amps) | Duty Cycle | Electrical Dwg. |
|------------------------------------------------------------------------|-----------------|------------------|-----------------|----------------------|--------------------------|------------------|----------------|------------|-----------------|
| <b>110 VAC ELECTRIC ACTUATED STAINLESS BALL VALVES, ON-OFF version</b> |                 |                  |                 |                      |                          |                  |                |            |                 |
| 585202                                                                 | 1/4             | 11.5             | 5.9             | 69                   | 20                       | 110 VAC, 50/60Hz | 0.27           | 70%        | B               |
| 585203                                                                 | 3/8             | 12.5             | 5.9             | 69                   | 20                       | 110 VAC, 50/60Hz | 0.27           | 70%        | B               |
| 585204                                                                 | 1/2             | 15               | 8.4             | 69                   | 20                       | 110 VAC, 50/60Hz | 0.27           | 70%        | B               |
| 585206                                                                 | 3/4             | 20               | 15.9            | 69                   | 20                       | 110 VAC, 50/60Hz | 0.27           | 70%        | B               |
| 585208                                                                 | 1               | 25               | 47.9            | 69                   | 20                       | 110 VAC, 50/60Hz | 0.27           | 70%        | B               |
| 585210                                                                 | 1-1/4           | 32               | 77.6            | 69                   | 20                       | 110 VAC, 50/60Hz | 0.27           | 70%        | B               |
| 585212                                                                 | 1-1/2           | 38               | 124.7           | 69                   | 20                       | 110 VAC, 50/60Hz | 0.27           | 70%        | B               |
| 585216A                                                                | 2               | 50               | 195.5           | 69                   | 30                       | 110 VAC, 50/60Hz | 0.63           | 70%        | B               |
| 585220                                                                 | 2-1/2           | 65               | 250.0           | 55                   | 30                       | 110 VAC, 50/60Hz | 0.63           | 70%        | B               |
| 585224                                                                 | 3               | 80               | 392.7           | 55                   | 30                       | 110 VAC, 50/60Hz | 0.63           | 70%        | B               |
| 585232                                                                 | 4               | 100              | 614.2           | 55                   | 30                       | 110 VAC, 50/60Hz | 0.63           | 70%        | B               |
| <b>24 VDC ELECTRIC ACTUATED STAINLESS BALL VALVES, ON-OFF version</b>  |                 |                  |                 |                      |                          |                  |                |            |                 |
| 585302                                                                 | 1/4             | 11.5             | 5.9             | 69                   | 20                       | DC24             | 1.8            | 70%        | G               |
| 585303                                                                 | 3/8             | 12.5             | 5.9             | 69                   | 20                       | DC24             | 1.8            | 70%        | G               |
| 585304                                                                 | 1/2             | 15               | 8.4             | 69                   | 20                       | DC24             | 1.8            | 70%        | G               |
| 585306                                                                 | 3/4             | 20               | 15.9            | 69                   | 20                       | DC24             | 1.8            | 70%        | G               |
| 585308                                                                 | 1               | 25               | 47.9            | 69                   | 20                       | DC24             | 1.8            | 70%        | G               |
| 585310                                                                 | 1-1/4           | 32               | 77.6            | 69                   | 20                       | DC24             | 1.8            | 70%        | G               |
| 585312                                                                 | 1-1/2           | 38               | 124.7           | 69                   | 20                       | DC24             | 1.8            | 70%        | G               |
| 585316A                                                                | 2               | 50               | 195.5           | 69                   | 30                       | DC24             | 2.4            | 70%        | G               |
| 585320                                                                 | 2-1/2           | 65               | 250.0           | 55                   | 30                       | DC24             | 2.4            | 70%        | G               |
| 585324                                                                 | 3               | 80               | 392.7           | 55                   | 30                       | DC24             | 2.4            | 70%        | G               |
| 585332                                                                 | 4               | 100              | 614.2           | 55                   | 30                       | DC24             | 2.4            | 70%        | G               |

\* Pressure range @ -18 to 38° C (reduced pressure for higher temperatures—see P/T chart)

## Specifications (Metric units)


| Stock Number                                                                        | Pipe Size (NPT) | Orifice Diameter (mm) | Kv Flow Factor* | Max Pressure (Bar)** | Cycle Time/90° (seconds) | Voltage          | Current (amps) | Duty Cycle | Electrical Dwg. |
|-------------------------------------------------------------------------------------|-----------------|-----------------------|-----------------|----------------------|--------------------------|------------------|----------------|------------|-----------------|
| <b>110 VAC ELECTRIC ACTUATED STAINLESS BALL VALVES, EPS POSITIONER 4-20mA input</b> |                 |                       |                 |                      |                          |                  |                |            |                 |
| 585402                                                                              | 1/4             | 11.5                  | 5.9             | 69                   | 20                       | 110 VAC, 50/60Hz | 0.27           | 70%        | E               |
| 585403                                                                              | 3/8             | 12.5                  | 5.9             | 69                   | 20                       | 110 VAC, 50/60Hz | 0.27           | 70%        | E               |
| 585404                                                                              | 1/2             | 15                    | 8.4             | 69                   | 20                       | 110 VAC, 50/60Hz | 0.27           | 70%        | E               |
| 585406                                                                              | 3/4             | 20                    | 15.9            | 69                   | 20                       | 110 VAC, 50/60Hz | 0.27           | 70%        | E               |
| 585408                                                                              | 1               | 25                    | 47.9            | 69                   | 20                       | 110 VAC, 50/60Hz | 0.27           | 70%        | E               |
| 585410                                                                              | 1-1/4           | 32                    | 77.6            | 69                   | 20                       | 110 VAC, 50/60Hz | 0.27           | 70%        | E               |
| 585412                                                                              | 1-1/2           | 38                    | 124.7           | 69                   | 20                       | 110 VAC, 50/60Hz | 0.27           | 70%        | E               |
| 585416A                                                                             | 2               | 50                    | 195.5           | 69                   | 30                       | 110 VAC, 50/60Hz | 0.63           | 70%        | E               |
| 585420                                                                              | 2-1/2           | 65                    | 250.0           | 55                   | 30                       | 110 VAC, 50/60Hz | 0.63           | 70%        | E               |
| 585424                                                                              | 3               | 80                    | 392.7           | 55                   | 30                       | 110 VAC, 50/60Hz | 0.63           | 70%        | E               |
| 585432                                                                              | 4               | 100                   | 614.2           | 55                   | 30                       | 110 VAC, 50/60Hz | 0.63           | 70%        | E               |
| <b>24 VDC ELECTRIC ACTUATED STAINLESS BALL VALVES, EPS POSITIONER 4-20mA input</b>  |                 |                       |                 |                      |                          |                  |                |            |                 |
| 585502                                                                              | 1/4             | 11.5                  | 5.9             | 69                   | 20                       | DC24             | 1.8            | 70%        | GEY             |
| 585503                                                                              | 3/8             | 12.5                  | 5.9             | 69                   | 20                       | DC24             | 1.8            | 70%        | GEY             |
| 585504                                                                              | 1/2             | 15                    | 8.4             | 69                   | 20                       | DC24             | 1.8            | 70%        | GEY             |
| 585506                                                                              | 3/4             | 20                    | 15.9            | 69                   | 20                       | DC24             | 1.8            | 70%        | GEY             |
| 585508                                                                              | 1               | 25                    | 47.9            | 69                   | 20                       | DC24             | 1.8            | 70%        | GEY             |
| 585510                                                                              | 1-1/4           | 32                    | 77.6            | 69                   | 20                       | DC24             | 1.8            | 70%        | GEY             |
| 585512                                                                              | 1-1/2           | 38                    | 124.7           | 69                   | 20                       | DC24             | 1.8            | 70%        | GEY             |
| 585516A                                                                             | 2               | 50                    | 195.5           | 69                   | 30                       | DC24             | 2.4            | 70%        | GEY             |
| 585520                                                                              | 2-1/2           | 65                    | 250.0           | 55                   | 30                       | DC24             | 2.4            | 70%        | GEY             |
| 585524                                                                              | 3               | 80                    | 392.7           | 55                   | 30                       | DC24             | 2.4            | 70%        | GEY             |
| 585532                                                                              | 4               | 100                   | 614.2           | 55                   | 30                       | DC24             | 2.4            | 70%        | GEY             |

\* Pressure range @ -18 to 38° C (reduced pressure for higher temperatures—see P/T chart)

## Pressure/Temperature Chart


### Pressure/Temp. Chart - 1000 PSI (69 Bar)

| P/T Chart (PSI/°F) |      |      |     |     |
|--------------------|------|------|-----|-----|
| PSI                | 1000 | 1000 | 100 | 0   |
| °F                 | -4   | 50   | 330 | 392 |




### Pressure/Temp. Chart - 800 PSI (55 Bar)

| P/T Chart (PSI/°F) |     |     |     |     |
|--------------------|-----|-----|-----|-----|
| PSI                | 800 | 800 | 100 | 0   |
| °F                 | -4  | 50  | 330 | 392 |




### Pressure/Temp. Chart - 69 Bar (1000 PSI)

| P/T Chart (BAR/°C) |     |    |     |     |
|--------------------|-----|----|-----|-----|
| Bar                | 69  | 69 | 7   | 0   |
| °C                 | -20 | 10 | 166 | 200 |



### Pressure/Temp. Chart - 55 Bar (800 PSI)

| P/T Chart (BAR/°C) |     |    |     |     |
|--------------------|-----|----|-----|-----|
| Bar                | 55  | 55 | 7   | 0   |
| °C                 | -20 | 10 | 166 | 200 |



## Electrical Wiring– On/Off

### ELECTRICAL WIRING

Confirm the actuator VOLTAGE is correct, then remove the terminal box cover and connect wiring to terminal strip according to appropriate wiring diagram.

For convenience, wiring diagrams for each actuator are attached to the inside of the terminal box cover.


User/installer to supply a three way switch, control relay, PLC outputs, or other suitable switching device to control the actuator position. Actuator should have its own fused and isolated circuit. Do not connect actuators in parallel.

Power should be maintained either in the open or closed position to activate the internal heater. This heater will help prevent condensation build-up inside the actuator.




Before connecting power, confirm correct VOLTAGE is being applied. Incorrect voltage may damage actuator and void the warranty.

#### AC Voltage Wiring Diagram



FOR SUPPLY CONNECTIONS, USE WIRES SUITABLE FOR  
AT LEAST 90°C (194°F) Employer Des Fils D'alimentation  
Qui Conviennent Pour Au Moins 90°C

#### DC Voltage Wiring Diagram



FOR SUPPLY CONNECTIONS, USE WIRES SUITABLE FOR  
AT LEAST 90°C (194°F) Employer Des Fils D'alimentation  
Qui Conviennent Pour Au Moins 90°C

#### AC Voltage Wiring:

[User/Installer to Supply Relay or 3-way Switch (K)]

Terminal 1: Power Neutral (N)

Terminal 2: Power (L) to terminal 2 - Actuator OFF or CLOSED

Terminal 3: Power (L) to terminal 3 - Actuator ON or OPEN

#### Auxiliary Position Confirmation Limit Switches

Terminal 4: Common

Terminal 5: Open status confirmation signal

Terminal 6: Closed status confirmation signal

#### Ground PE

Terminal 7: Earth Ground

**NOTES:** 1. Auxiliary limit switches are rated 3A@125/250VAC, 30VDC resistive load. 2. Actuator should have its own fused and isolated circuit. Do not wire actuators in parallel.

#### DC Voltage Wiring:

[User/Installer to Supply Reversing Relay or Switch]

Terminal 1: Power Positive (+) to close, power Negative (-) to open

Terminal 2: Power Negative (-) to close, power Positive (+) to open

#### Auxiliary Position Confirmation Limit Switches

Terminal 3: Common

Terminal 4: Open status confirmation signal

Terminal 5: Closed status confirmation signal

#### Ground PE


Terminal 7: Earth Ground

## Electrical Wiring– EPS Positioner

Confirm the actuator VOLTAGE is correct, then remove the terminal box cover and connect wiring to terminal strip according to appropriate wiring diagram.

Wiring diagrams for each actuator are attached to the inside of the terminal box cover.

Input control signal type is 4-20mA. Actuator should have its own fused and isolated circuit. Do not connect actuators in parallel. Power to actuator should be maintained to activate the internal heater. This heater will help prevent condensation build-up inside the actuator.




### OPERATION (EPS ONLY)

Valworx 5818 series electric actuators with EPS- Electronic Positioning System provide an accurate valve positioning function whereby the movement of the actuator is controlled by a 4-20mA input control signal. Any change in the control input signal results in a corresponding and proportional change in the position of the actuator drive output..

This is achieved with a unique built in electronic positioning module. The module is fully potted to help protect the electronics from vibration and moisture.

An internal microprocessor on the EPS circuit board continuously monitors the analog input and output signals and compares them to the physical position via a precision potentiometer feedback system, moving the drive output as required to balance the signals

**AC Voltage Wiring Diagram**



FOR SUPPLY CONNECTIONS, USE WIRES SUITABLE FOR AT LEAST 90°C (194°F) Employer Des Fils D'alimentation Qui Convienent Pour Au Moins 90°C


### AC Voltage Wiring:

1. AC power - Neutral
2. AC power - Line/Hot
3. Input control signal - Negative (-)
4. Input control signal - Positive (+)
5. Output monitoring signal - Negative (-)
6. Output monitoring signal - Positive (+)

### EPS POSITIONER TECHNICAL DATA

Input Signal: 4-20mA  
Output Signal: 4-20mA  
Deadband: 0.5% to 5.0%

**DC Voltage Wiring Diagram**




FOR SUPPLY CONNECTIONS, USE WIRES SUITABLE FOR AT LEAST 90°C (194°F) Employer Des Fils D'alimentation Qui Convienent Pour Au Moins 90°C

### DC Voltage Wiring:

1. DC power - Negative (-)
2. DC power - Positive (+)
3. Input control signal - Negative (-)
4. Input control signal - Positive (+)
5. Output monitoring signal - Negative (-)
6. Output monitoring signal - Positive (+)


**NOTES:** 1. Actuator should have its own fused and isolated circuit. 2. Do not wire actuators in parallel. 3. Output signal is 4-20mA. Use of the output is optional.

## Dimensions: 1/4" - 2" (On/Off & EPS)



| Pipe Size (NPT) |      | A     | C     | D     | E    | H     | J     | K    | M    | P    | Weight  |
|-----------------|------|-------|-------|-------|------|-------|-------|------|------|------|---------|
| 1/4             | inch | 6.7   | 3.9   | 2.6   | 1.5  | 6.2   | 6.8   | 1.2  | 0.6  | 0.5  | 8.4 lb  |
|                 | mm   | 170.5 | 99.5  | 65.3  | 37.0 | 157.5 | 172.7 | 31.0 | 15.0 | 11.5 | 3.8 kg  |
| 3/8             | inch | 6.7   | 3.9   | 2.6   | 1.5  | 6.2   | 6.8   | 1.2  | 0.6  | 0.5  | 8.4 lb  |
|                 | mm   | 170.5 | 99.5  | 65.3  | 37.0 | 157.5 | 172.7 | 31.0 | 15.0 | 12.5 | 3.8 kg  |
| 1/2             | inch | 6.7   | 3.9   | 2.6   | 1.5  | 6.2   | 6.8   | 1.2  | 0.6  | 0.6  | 8.3 lb  |
|                 | mm   | 170.5 | 99.5  | 65.3  | 37.0 | 157.5 | 172.7 | 31.0 | 15.0 | 15.0 | 3.7 kg  |
| 3/4             | inch | 6.7   | 3.9   | 3.0   | 1.8  | 6.5   | 7.3   | 1.5  | 0.6  | 0.8  | 8.7 lb  |
|                 | mm   | 170.5 | 99.5  | 77.3  | 45.0 | 165.1 | 185.4 | 38.9 | 15.0 | 20.0 | 3.9 kg  |
| 1               | inch | 6.7   | 3.9   | 3.5   | 2.1  | 6.8   | 7.8   | 1.7  | 0.6  | 1.0  | 9.4 lb  |
|                 | mm   | 170.5 | 99.5  | 88.7  | 53.5 | 172.7 | 198.1 | 44.3 | 15.0 | 25.0 | 4.3 kg  |
| 1-1/4           | inch | 6.7   | 3.9   | 4.0   | 2.3  | 7.0   | 8.3   | 2.0  | 0.6  | 1.3  | 10.4 lb |
|                 | mm   | 170.5 | 99.5  | 102.4 | 59.0 | 177.8 | 210.8 | 50.7 | 15.0 | 32.0 | 4.7 kg  |
| 1-1/2           | inch | 6.7   | 3.9   | 4.3   | 2.9  | 7.6   | 9.1   | 2.2  | 0.6  | 1.5  | 12.0 lb |
|                 | mm   | 170.5 | 99.5  | 109.0 | 74.8 | 193.0 | 231.1 | 55.0 | 15.0 | 38.0 | 5.4 kg  |
| 2               | inch | 8.6   | 4.5   | 4.9   | 3.3  | 9.2   | 11.0  | 2.4  | 0.6  | 2.0  | 20.3 lb |
|                 | mm   | 217.5 | 114.0 | 125.3 | 83.5 | 233.7 | 279.4 | 62.2 | 15.0 | 50.0 | 9.2 kg  |

Dimensions: 2-1/2" - 4" (On/Off & EPS)



| Pipe Size (NPT) |      | A     | C     | D     | E     | H     | J     | K     | M    | P     | Weight  |
|-----------------|------|-------|-------|-------|-------|-------|-------|-------|------|-------|---------|
| 2-1/2           | inch | 8.6   | 4.5   | 6.5   | 4.3   | 10.2  | 12.2  | 3.2   | 0.6  | 2.6   | 27.7 lb |
|                 | mm   | 217.5 | 114.0 | 165.0 | 108.8 | 259.1 | 309.9 | 82.5  | 15.0 | 65.0  | 12.6 kg |
| 3               | inch | 8.6   | 4.5   | 7.5   | 4.7   | 10.6  | 13.2  | 3.7   | 0.6  | 3.1   | 33.7 lb |
|                 | mm   | 217.5 | 114.0 | 189.5 | 118.3 | 269.2 | 335.3 | 94.8  | 15.0 | 80.0  | 15.3 kg |
| 4               | inch | 8.6   | 4.5   | 9.4   | 6.1   | 12.0  | 15.2  | 4.7   | 0.6  | 3.9   | 48.8 lb |
|                 | mm   | 217.5 | 114.0 | 238.0 | 153.8 | 304.8 | 386.1 | 119.0 | 15.0 | 100.0 | 22.1 kg |